



900099 Lube

Powder-Coated Housing

Used For

- Engine Oil

Capacity & Flow Rate

- Requires 16 Qt./15.1 L. of makeup fluid (housing volume)
- *Ideal sump range from 12-15 Gal./45.4-56.8 L.
- **Flow rate range from 0-1.25 GPM/0-4.7LPM

Overall Dimensions & Weight

- 19.25" (H) *Plus 18" clearance above to change filter*
- 10.62" (W)
- 10.75" (D)
- 27 LB. shipping weight

Other Specifications

- Max operating pressure, 80 PSI
- 1/2" FNPT inlet, outlet & drain ports
- ***Powder-coating inside and outside of housing
- Use with petroleum or synthetic fluids

Notes

- **Flow rates are established using ISO 10-1000 viscosity oils at the standard 40° C/104° F and are subject to vary
- *Viscosity, operating temperature, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, elements need to be changed between 500-1000 hours for optimal performance, ideally change the element when the flow is half the starting flow or the PSI is double the starting PSI
- Available option for water-based lubricants
- ***Available in stainless-steel



Recommended Element

- Model 7502 for SAE: 0W, 5W, 10W, 15W, 20, 30, 40
- Model 7504 for SAE: 50

Harvard Corporation is able to meet many custom requirements, please contact Lubrication Technologies 413-788-5823 for more information.

45 YEARS **LUBRICATION Technologies**
AN UNCOMMON TECHNICAL RESOURCE
(413) 788-LUBE (5823)
www.LubeTechnologies.com
AUTHORIZED DISTRIBUTOR