



900185 Bag Filter

Powder-Coated Housing

Used For

- Diesel Fuel
- Hydraulic Oil
- Cutting Oil
- Fluids with large contamination particles
- Oil or Water-Based Fluids and Fuels

Capacity & Flow Rate

- Requires 20 Qt./18.9 L. of makeup fluid (housing volume)
- *Ideal sump range from 0-250 Gal./0-946.4 L.
- *Flow rate range from 0-50 GPM/0-189.3 LPM

Overall Dimensions & Weight

- 23.87" (H) *Plus 20" clearance above to change filter*
- 10.62" (W)
- 10.75" (D)
- 29 LB. shipping weight

Other Specifications

- Max operating pressure, 80 PSI
- 1 1/2" FNPT inlet, outlet ports, 1/2" FNPT drain port
- **Powder-coating inside and outside of housing
- Stainless-steel basket pre-installed, *part # 2877*
- Use with petroleum or synthetic fluids, diesel fuel, & water-based fluids

Notes

- *Viscosity, operating temperature, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, bag filters need to be changed when the bag filter is full, ideally change the bag filter when the vacuum gauge reads between 2-3 times what the starting gauge reading was
- **Available in stainless-steel, *part # 900238*
- Available regular and rare earth magnet ring inserts (regular #3639) (rare earth # 3628)



Recommended Bag Filter use for all viscosities

- | | |
|-----------------------|-------------------------------|
| • Model 566 5 Micron | • Model 571 75 Micron |
| • Model 578 10 Micron | • Model 572 100 Micron |
| • Model 568 15 Micron | • Model 3617 150 Micron |
| • Model 569 25 Micron | • Model 3892 200 Micron |
| • Model 570 50 Micron | • Customizable 3-layer option |



AN UNCOMMON TECHNICAL RESOURCE

(413) 788-LUBE (5823)

www.LubeTechnologies.com

AUTHORIZED DISTRIBUTOR