



# 900238 Bag Filter

## Stainless-Steel Housing

### Used For

- Diesel Fuel
- Hydraulic Oil
- Cutting Oil
- Fluids with large contamination particles
- Oil or Water-Based Fluids and Fuels

### Capacity & Flow Rate

- Requires 20 Qt./18.9 L. of makeup fluid (housing volume)
- \*Ideal sump range from 0-250 Gal./0-946.4 L.
- \*Flow rate range from 0-50 GPM/0-189.3 LPM

### Overall Dimensions & Weight

- 23.87" (H) *Plus 20" clearance above to change filter*
- 10.62" (W)
- 10.75" (D)
- 29 LB. shipping weight

### Other Specifications

- Max operating pressure, 80 PSI
- 1 1/2" FNPT inlet, outlet ports, 1/2" FNPT drain port
- \*\*Made from stainless-steel
- Stainless-steel basket pre-installed, *part # 2877*
- Use with petroleum or synthetic fluids, diesel fuel, & water-based fluids

### Notes

- \*Viscosity, operating temp, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, bag filters need to be changed when the bag filter is full, ideally change the bag filter when the vacuum gauge reads between 2-3 times what the starting gauge reading was
- \*\*Available with powder-coated inside and outside, *part # 900185*
- Available regular and rare earth magnet ring inserts (regular #3639) (rare earth # 3628)



### Recommended Bag Filter use for all viscosities

- |                       |                               |
|-----------------------|-------------------------------|
| • Model 566 5 Micron  | • Model 571 75 Micron         |
| • Model 578 10 Micron | • Model 572 100 Micron        |
| • Model 568 15 Micron | • Model 3617 150 Micron       |
| • Model 569 25 Micron | • Model 3892 200 Micron       |
| • Model 570 50 Micron | • Customizable 3-layer option |

Harvard Corporation is able to meet many custom requirements, please contact Lubrication Technologies 413-788-5823 for more information.

**45 YEARS** **LUBRICATION Technologies Inc.**  
**AN UNCOMMON TECHNICAL RESOURCE**  
**(413) 788-LUBE (5823)**  
**[www.LubeTechnologies.com](http://www.LubeTechnologies.com)**  
**AUTHORIZED DISTRIBUTOR**